



SOLIVIA 15 TL

High efficiency 3-phase solar inverters for the European market -
Perfect choice for medium sized systems, such as those frequently
used in the commercial or agricultural sectors

Versatile applications

- Aluminium housing ensures long lasting protection against moisture and corrosion
- Wide input voltage range
- Suitable for indoor and outdoor applications (IP65)

Maximum profitability

- Peak efficiency of 98.0 %
- Full output power up to 40 °C
- 2 MPP trackers - symmetrical and asymmetrical loading possible (33/67 %)
- 10 years guarantee after online registration

15 kW transformerless solar inverters

Technical data SOLIVIA 15 TL

INPUT (DC)	SOLIVIA 15 EU G4 TL
Max. recommended PV power	19 kW _p ¹⁾
Nominal power	15.3 kW
Voltage range	250 ... 1000 V
Full power MPP range	350 ... 800 V
Max. current	48 A (24 A per MPP tracker)
Max. number of MPP trackers	Parallel inputs: 1 MPP tracker Separate inputs: 2 MPP trackers
Input load	Symmetrical and asymmetrical (33/67 %)

OUTPUT (AC)	
Nominal apparent power	15 kVA ²⁾
Voltage range	3 x 230 / 400 V (± 20 %) + N + PE ³⁾
Nominal current (per phase)	22 A
Nominal frequency	50 / 60 Hz
Frequency range	50 / 60 Hz ± 5 Hz ³⁾
Power factor adjustable	0.8 cap ... 0.8 ind
Total harmonic distortion (THD)	< 3 % @ nominal apparent power

GENERAL SPECIFICATION

Model name	SOLIVIA 15 EU G4 TL ⁴⁾
Part number Delta	EOE48010362
Max. efficiency	98 %
Efficiency EU	> 97.8 %
Operating temperature	-20 ... +60 °C
Full power without derating	-20 ... +40 °C
Storage temperature	-20 ... +70 °C
Humidity	0 ... 90 %
Max. operating altitude	2000 m (above sea level)

MECHANICAL DESIGN

Size (L x W x D)	952 x 625 x 275 mm
Weight	67.2 kg
Cooling	Fan
AC connector	Amphenol C16/3
DC connector	4 pairs of Multi-Contact MC4
Communication interfaces	2 x RJ45 / RS485
DC disconnect	Integrated
Display	5" monochrome graphical LCD

SAFETY / STANDARDS	SOLIVIA 15 EU G4 TL
Protection degree	IP65 / IP55 ⁵⁾
Safety class	I
Configurable trip parameters	Yes
Insulation monitoring	Yes
Overload behavior	Current limitation; power limitation
Anti-islanding protection / Grid regulation	AS 4777; BDEW; CEI 0-21; EN 50438; France/islands 60 Hz; G59/1-2 (230 V & 240 V); RD661/2007; RD1699/2011; SONDO Class C; Synergrid C10/C11 06/2012; UTE C15-712-1; VDE-0126-1-1/A1; VDE-AR-N 4105; VFR 2013; VFR 2014; ⁶⁾
EMC	EN61000-6-2; EN61000-6-3; EN61000-3-11; EN61000-3-12; C-Tick
Safety	IEC62109-1 / -2; CE compliance; AS/NZS 3100

- 1) When operated with balanced input load (50/50 %)
- 2) Cos Phi = 1 (VA = W)
- 3) AC voltage and frequency range will be programmed according to the individual country requirements.
- 4) An overview of our inverters that can be installed in your country can be found on our website www.solar-inverter.com.
- 5) IP65 for electronics / IP55 for cooling area
- 6) Please check our website at www.solar-inverter.com for the latest country grid list.

United Kingdom

Email: sales.uk@solar-inverter.com
Tel: 0800 051 4280 (Free Call)

International

Email: sales.europe@solar-inverter.com
Tel: +49 7641 455 547

